AUTODOC CLUB

How to change spark plugs on **MERCEDES-BENZ C-Class Coupe (CL203)** – replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle


Important!

This replacement procedure can be used for:
MERCEDES-BENZ C-Class Coupe (CL203) C 180 (203.735), MERCEDES-BENZ C-Class Coupe (CL203) C 200 Kompressor (203.745), MERCEDES-BENZ C-Class Coupe (CL203) C 230 Kompressor (203.747)

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: MERCEDES-BENZ C-Class Saloon (W203) C 200 Kompressor (203.045)

REPLACEMENT: SPARK PLUGS – MERCEDES-BENZ C-CLASS COUPE (CL203). TOOLS YOU MIGHT NEED:



- Electronic spray
- HEX bit No.HW5.
- Drive socket # E8
- Spark plug socket # 16
- Ratchet wrench
- Torque wrench
- High-temperature anti-seize lubricant
- Fender cover

Buy tools

Replacement: spark plugs – MERCEDES-BENZ C-Class Coupe (CL203). Professionals recommend:


- The replacement procedure is the same for all spark plugs.
- Warning! Shut down the engine before starting any work – MERCEDES-BENZ C-Class Coupe (CL203).

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1 Open the hood.

2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.

3 Undo the engine cover screws (3 pieces). Use HEX No.HW5.



4 Remove the engine cover.



5 Unscrew the fasteners of the ignition coils. Use a drive socket #E8.



6

Take out the ignition coils from the spark plug wells.




Replacement: spark plugs – MERCEDES-BENZ C-Class Coupe (CL203). Tip from AUTODOC:

- Remember the sequence of steps for ignition coil demounting.


7

Clean dirt, dust and debris from inside the spark plug wells.




8

Unscrew the spark plugs. Use the spark plug socket #16. Use a ratchet wrench.



9

Take out the spark plugs.



10 Apply a thin layer of a special high temperature anti-seize lubricant to the threads of the new spark plugs. Treat the surface of the terminals of the new spark plugs. Use electronic spray.



11 Install the new spark plugs into their mounting seats.




12 Screw new spark plugs and tighten them. Use the spark plug socket #16. Use a torque wrench. Tighten it to 28 nm torque.



Replacement: spark plugs – MERCEDES-BENZ C-Class Coupe (CL203). Professionals recommend:

- Don't tighten the plugs with excessive force. Exceeding tightening torque can damage the thread connection.
- Be careful when working with a spark plug wrench. Its skewing can cause damage to the threaded connection.


13 Install the ignition coils to the spark plug wells. Make sure you hear a click indicating that it is locked in place.




AUTODOC recommends:

- Replacement: spark plugs – MERCEDES-BENZ C-Class Coupe (CL203). Follow the installation steps.

14 Tighten the fasteners of the ignition coils. Use a drive socket #E8. Use a torque wrench. Tighten it to 9 Nm torque.




15 Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.



16 Shut off the engine.

17 Install the engine cover and secure it. Use HEX No.HW5. Use a ratchet wrench.



18 Remove the fender protection cover.


19 Close the hood.

WELL DONE!

VIEW MORE TUTORIALS

AUTODOC — TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

SPARK PLUGS: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.